

LED DRIVERS

Vol. 2013

www.dstifac.com

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST3W-MR16-DG03600	12V/24VAC	DC 2-5V	600mA±3%	1*3W	90%	0.65	1-500pcs		
DST3W-MR16-DG10300	12V/24VAC	DC 5-11V	300mA±3%	3*1W	90%	0.65	500-1Kpcs		
DST3W-MR16-DG10450	12V/24VAC	DC 5-11V	450mA±3%	3*2W	90%	0.65	1K-2Kpcs		
Dimension	Certified		Hard wire		Dimmable Type			Weight	
L14mm * W12mm * H18mm	RoHS		MR16		TRIAC			3g	
<p>This product is especially designed for MR16 spotlight, it can realize low voltage adjustable silicone brightness adjustment according to electronic transformer It can realize LED lighting adjustment application needs according to low voltage brightness equipment.</p>									
Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST3W-DG10300	110V/230VAC	DC6-11V	300mA±3%	1*3W	75%	0.9	1-500pcs		
							500-1Kpcs		
							1K-2Kpcs		
Dimension	Certified		Hard wire		Dimmable Type			Weight	
L25mm * W18mm * H14mm	RoHS		4Wire		TRIAC/SCR			8g	
<p>This product is especially designed for GU10/E27/E26 LED spotlight, it is with high compatiability. It is compatiabile with most brands adjustable silicone. High power factor will reduce bad infuence to power supply system. Good and cheap prices with high availability. If the raditor is not well, it will result in electronic circuit temperature arise wich cause in current swift</p>									

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST7W-MR16-DG10480	12V/24VAC	DC 6-11V	480mA±3%	2*3*2W	78%	0.65	1-500pcs		
DST7W-MR16-DG23300	12V/24VAC	DC 5-11V	300mA±3%	4*7*1W	78%	0.65	500-1Kpcs	1K-2Kpcs	
Dimension	Certified		Hard wire		Dimmable Type			Weight	
L54mm * W22mm * H15mm	CE/FCC/CC/UL/GS/CSA/RoHS		4Wire		TRIAC/SCR			23g	

This product is especially designed for G70/G60and G50 whose base are GU10/E27's bulb It use the traditional adjustable silicome to realize dimming, Imported IC and high quality electronic components will stabilize quality and adjust current. Passed with CE/FCC/CC/UL.GS/CSA certificates. It is compatible with most brands dimmer. It is the best LED power sply driver at the present

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST9W-DG14450	110/230VAC	DC 6-14V	500mA±3%	2-4*2W	87%	0.92	1-500pcs		
DST9W-DG10600	110/230VAC	DC 6-11V	600mA±3%	2-3*3W	87%	0.92	500-1Kpcs		
DST9W-DG30300	110/230VAC	DC 12-30V	350mA±3%	6-9*1W	87%	0.92	1K-2Kpcs		
Dimension	Certified		Hard wire		Dimmable Type			Weight	
L54mm * W23mm * H18mm	RoHS		4Wire		TRIAC/SCR			27g	

it is especially designed for G70/G60and G50 whose base are GU10/E27's bulb It use the traditional adjustable silicome to realize dimming, Imported IC and high quality electronic components will stabilize quality and adjust current. Passed with CE/FCC/CC/UL.GS/CSA certificates. It is compatible with most brands immer. It is the best LED power supply driver at the present. American national semiconductor proposal

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST15W-DG21700	110/230VAC	DC15-25V	700mA±3%	4-7*3W	80%	0.85	1-500pcs		
DST15W-21500	110/230VAC	DC15-25V	500mA±3%	4-7*2W	80%	0.85	500-1Kpcs		
SdT15W-DG50300	110/230VAC	DC30-50V	350mA±3%	10-15*1W	80%	0.85	1K-2Kpcs		
Dimension	Certified		Hard wire		Dimmable Type			Weight	
L68mm * W52/32/19mm * H22mm	CE/FCC/CC/UL/GS/CSA/RoHS		4wire		TRIAC/SCR			55g	

This product is especially designed for PAR38/PAR30/G56/AR111 whose base are GU10/E27's bulb It use the traditional adjustable silicome to realize dimming, Imported IC and high quality electronic components will stabilize quality and adjust current. Passed with CE/FCC/CC/UL.GS/CSA certificates. It is compatible with most brands dimmer. It is the best LED power supply driver at the present. IW 3612 proposal

DIMMABLE LED DRIVER (Close structure)

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST3W-D10300	100-240VAC	DC 5-11V	300mA±3%	3*1W	75%	0.65	1-500pcs		
							500-1Kpcs	1K-2Kpcs	
Dimension	Certified		Hard wire		Dimmable Type			Weight	
L37mm * W21mm * H26mm	PSE/RoHS		4WIRE		TRIAC/SCR			30g	

It is especially designed forLED ceiling lmap and down light. It sue the traditional adjustable silicome to adjust 20mA (3%~100%) start curret for dimming. Inner and high stable IC will control and avoid current swift. The

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST7W-D10500	100-230VAC	DC 6-115V	480mA±3%	2-3*2W	78%	0.65	1-500pcs		
DST7W-D23300	100-230VAC	DC 12-24V	300mA±3%	4-7*1W	78%	0.65	500-1Kpcs	1K-2Kpcs	
Dimension	Certified		Hard wire		Dimmable Type			Weight	
L65mm * W35mm * H23mm	RoHS		4WIRE		TRIAC/SCR			70g	

It is especially designed forLED ceiling lmap and down light. It sue the traditional adjustable silicome to adjust 20mA (3%~100%) start curret for dimming. Inner and high stable IC will control and avoid current swift. It is the best LED power supply driver at the present. American national semiconductor proposal

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST10W-D10500	110/230VAC	DC6-14V	500mA±3%	2-4*2W	80%	0.65	1-500pcs		
DST10W-D10650	110/230VAC	DC6-11V	650mA±3%	2-3*3W	80%	0.65	500-1Kpcs		
DST10W-D35300	110/230VAC	DC18-35V	300mA±3%	6-10*1W	80%	0.65	1K-2Kpcs		
Dimension	Certified		Hard wire		Dimmable Type			Weight	
L88mm * W39mm * H23mm	RoHS		TERMINAL		TRIAC/SCR			80g	

It is especially designed forLED ceiling lmap and down light. It sue the traditional adjustable silicome to adjust 20mA (3%~100%) start curret for dimming. Inner and high stable IC will control and avoid current swift. It is the best LED power supply driver at the present. American national semiconductor proposal

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST15W-D21700	110/230VAC	DC15-25V	700mA±3%	4-7*3W	80%	0.75	1-500pcs		
DST15W-D21500	110/230VAC	DC15-25V	500mA±3%	4-7*2W	80%	0.75	500-1Kpcs		
DST15W-D50300	110/230VAC	DC27-50V	300mA±3%	9-15*1W	80%	0.75	1K-2Kpcs		
Dimension	Certified		Hard wire		Dimmable Type			Weight	
L115mm * W45mm * H28mm	RoHS		4WIRE		TRIAC/SCR			95g	

It is especially designed for external LED ceiling lamp and downlight. It use the traditional adjustable silicome to realize dimming, Imported IC and high quality electronic components will stabilize quality and adjust current, Passed with CE/FCC/GS/CSA certificates.. Compatible with most brands dimmer. It is the best LED power supply driver with good compatibility at market at the present. IW 3612 proposal

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST25W-D36700	110/230VAC	DC21-36V	700mA±3%	7-10*3W	82%	0.85	1-500pcs		
DST25W-D40500	110/230VAC	DC25-40V	500mA±3%	8-12*2W	82%	0.85	500-1Kpcs		
DST25W-D70300	110/230VAC	DC50-70V	300mA±3%	16-25*1W	82%	0.85	1K-2Kpcs		
Dimension	Certified		Hard wire		Dimmable Type			Weight	
L140mm * W45mm * H28mm	RoHS		TERMINAL		TRIAC/SCR			120g	

It is especially designed for external LED ceiling lamp and downlight. It use the traditional adjustable silicome to realize dimming, Imported IC and high quality electronic components will stabilize quality and adjust current, Passed with CE/FCC/GS/CSA certificates.. Compatible with most brands dimmer. It is the best LED power supply driver with good compatibility at market at the present. IW 3612 proposal

NON-ISOLATION LED TUBE DRIVER (6-20W)

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST-BHH240	110/240VAC	DC36-80V	200-240mA±3%	12P*12-25S	93%	0.97	1-500pcs		<p>H10mm L160mm W16mm</p>
DST-BHH120	110/240VAC	DC36-80V	100-120mA±3%	6P*12-25S	93%	0.97	500-1Kpcs		
DST-BHH300	110/240VAC	DC40-60V	280-300mA±3%	16P*12-25S	93%	0.97	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit Type		Weight		
L150mm * W16mm * H10mm	RoHS		T8 LED TUBE LED		NON-ISOLATION		60g		

non-isolated circuit design. Suitable the low heat. Voltage reduction power supply. Change the AC to DC in high voltage. Use the buck circuit to reduce voltage and make constant current control and control voltage reduction. High efficiency. Low costs and high power factor. Output voltage could be automatically adjustable and applicable within the design areas.

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST-BLL	110/240VAC	DC30-50V	60-170mA±3%		89%	0.95	1-500pcs		<p>H10mm L160mm W16mm</p>
DST-BLL	110/240VAC	DC50-80V	180-240mA±3%		89%	0.95	500-1Kpcs		
DST-BLL	110/240VAC	DC30-50V	250-400mA±3%		89%	0.95	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit Type		Weight		
L125mm * W18mm * H10mm	RoHS		T8 LED TUBE LED		Non-isolation		60g		

non-isolated circuit design. Suitable the low heat. Voltage reduction power supply. Change the AC to DC in high voltage. Use the buck circuit to reduce voltage and make constant current control and control voltage reduction. High efficiency. Low costs and high power factor. Output voltage could be automatically adjustable and applicable within the design areas.

UL MARKS ULTRATHIN ISOLATION LED TUBE DRIVER (15-30W)

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST-AP30W630	100-240VAC	DC 30-42V	630mA±3%	35P*10-12S	90%	0.98	1-500pcs	5.0	<p>H8.5mm L270mm W18mm</p>
DST-AP30W600	100-240VAC	DC 30-42V	600mA±3%	30P*10-12S	90%	0.98	500-1Kpcs	4.9	
DST-AP30W480	100-240VAC	DC 30-42V	480mA±3%	25P*10-12S	90%	0.98	1K-2Kpcs	4.7	
DST-AP30W320	100-240VAC	DC 30-42V	320mA±3%	22P*10-12S	90%	0.98			
Dimension	Certified		Hard wire		Circuit Type		Weight		
L270mm * W18mm * H8.5mm	UL/FCC/PSE/TUV/RoHS		T8/T10 LED TUBE LED		Isolation Circuit		100g		

It is the technology updated basing on DSTITAC's power present LED tube power supply driver. Ultra thin whose thickness is only 8.5mm. The input voltage is 12-30W. High efficiency. Low temperature arise. High stability and good craftsmanship. Compliance with China, Europe unions's first class efficiency standard. Compliance with Energy Star and CE currents compulsory standard

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST-AP32W630	100-240VAC	DC 30-60V	630mA±3%	35P*10-12	91%	0.98	1-500pcs		<p>H8.5mm L270mm W18mm</p>
DST-AP32W480	100-240VAC	DC 30-60V	480mA±3%	30P*10-12	91%	0.98	500-1Kpcs		
DST-AP32W450	100-240VAC	DC 30-60V	450mA±3%	25P*10-12	91%	0.98	1K-2Kpcs		
DST-AP32W400	100-240VAC	DC 30-60V	400mA±3%	22P*10-12	91%	0.98			
Dimension	Certified		Hard wire		None-dimmable		Weight		
L264mm * W17.5mm * H10.3mm	UL/FCC/PSE/TUV/RoHS		T8/T10 LED TUBE LED		Isolation Circuit		100g		

It is the technology updated basing on DSTITAC's power present LED tube power supply driver. Ultra thin whose thickness is only 8.5mm. The input voltage is 12-30W. High efficiency. Low temperature arise. High stability and good craftsmanship. Compliance with China, Europe unions's first class efficiency standard. Compliance with Energy Star and CE currents compulsory standard

DIMMABLE LED TUBE DRIVER (6-20W)

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST-D20W240	200-240VAC	DC 30-80V	240mA±3%	21P*10-25S	88-90%	0.96	1-500pcs		<p>H10mm L310mm W18mm</p>
DST-D20W200	200-240VAC	DC 30-80V	200mA±3%	18P*10-25S	88-90%	0.96	500-1Kpcs		
DST-D20W140	200-240VAC	DC 30-80V	140mA±3%	6P*10-25S	88-90%	0.96	1K-2Kpcs		
DST-D20W100	200-240VAC	DC 30-80V	100mA±3%	4P*10-25S	88-90%	0.96			
Dimension	Certified		Hard wire		None-dimmable		Weight		
L310mm * W18mm * H10mm	RoHS		T8/T10 LED TUBE LED		Isolation Circuit		70g		

This product is especially designed for MR16 spotlight, it can realize low voltage adjustable silicone brightness adjustment according to electronic transformer It can realize LED lighting adjustment application needs according to low voltage brightness equipment.

NONE-ISOLATION LED T10 TUBE DRIVER (15-30W)

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST-BHP30W430	170-240VAC	DC 40-80V	430mA±3%	24P*12-25	88-90%	0.98	1-500pcs		<p>H10mm L257mm W18mm</p>
DST-BHP30W360	170-240VAC	DC 40-80V	360mA±3%	20P*12-25	88-90%	0.98	500-1Kpcs		
DST-BHP30W320	170-240VAC	DC 40-80V	320mA±3%	18P*12-25	88-90%	0.98	1K-2Kpcs		
DST-BHP30W260	170-240VAC	DC 40-80V	260mA±3%	14P*12-25	88-90%	0.98			
Dimension	Certified		Hard wire		None-dimmable		Weight		
L275mm * W18mm * H110mm	RoHS		T8/T10 LED TUBE LED		Isolation Circuit		80g		

Using high current design. New updated product from original non isolated model. Output current could be ordered automatically within 20-240mA.

CLOSE FRAME CONSTANT CURRENT LED DRIVER

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST3W-AW03650	100-240VAC	DC 2-5V	650mA±3%	1*3W	75%	0.65	1-500pcs		<p>H20mm L57mm W25mm</p>
DST3W-AW10300	100-240VAC	DC 5-11V	300mA±3%	3*1W	75%	0.65	500-1Kpcs		
DST3W-AW3300	100-240VAC	DC 2-5V	300mA±3%	1*1W	75%	0.65	1K-2Kpcs		
Dimension	Certified		Hard wire		Waterproof Grade		Weight		
L85mm * W40mm * H25mm	CE/RoHS		4WIRE		IP65		70g		

It is especially designed for LED ceiling lamp and downlight so on. It can be waterproof or non-waterproof. Imported chips with stable quality. Smart& elegant-High constant current accuracy. Full protection abilities High charaters. Low noise. Long life. They can drive 3 pcs LED strings on cool white in series and other high LED lamps of the same current and voltage

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST15W-AP21650	100-240VAC	DC 12-24V	650mA±3%	4-7*3W	80%	0.94	1-500pcs		
DST15W-AP21500	100-240VAC	DC 12-24V	650mA±3%	5-7*2W	80%	0.94	500-1Kpcs		
DST15W-AP21300	100-240VAC	DC 12-24V	650mA±3%	10-15*1W	80%	0.94	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L85mm * W40mm * H35mm	UL/FCC/PSE/TUV/RoHS		4WIRE		Isolation circuit			70g	

It is European standard design. It can pass safety and strength tests. No lines are exposed. It is especially designed for LED ceiling lamps and downlights. Imported chis with good stability. Smart and elegant. High constand current accuracy. High efficiency. Stable ability. Low noise and long life. It can directly driver 10-15 pcs 1W LED cool white strings in series and other external LED lmap of the same current and voltage

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST12W-AP14650	100-240VAC	DC 6-14V	650mA±3%	2-4*3W	78%	0.82	1-500pcs		
DST12W-AP14500	100-240VAC	DC 6-14V	500mA±3%	2-4*2W	78%	0.82	500-1Kpcs		
DST12W-AP130320	100-240VAC	DC 18-43V	320mA±3%	6-12*1W	78%	0.82	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L88mm * W39mm * H23mm	SAA/SGS/PSE/TUV/RoHS		TERMINAL		Isolation circuit			60g	

It is European standard design. It can pass safety and strength tests. No lines are exposed. It is especially designed for LED ceiling lamps and downlights. Imported chis with good stability. Smart and elegant. High constand current accuracy. High efficiency. Stable ability. Low noise and long life. It can directly driver 10-15 pcs 1W LED cool white strings in series and other external LED lmap of the same current and voltage

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST12W-CE30320	100-240VAC	DC 20-40V	320mA±3%	6-12*1W	88%	0.97	1-500pcs		
							500-1Kpcs		
							1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L88mm * W39mm * H23mm	SAA/SGS/PSE/TUV/RoHS		TERMINAL		Isolation circuit			60g	

It is European standard design. It can pass safety and strength tests. No lines are exposed. It is especially designed for LED ceiling lamps and downlights. Imported chis with good stability. Smart and elegant. High constand current accuracy. High efficiency. Stable ability. Low noise and long life. It can directly driver 6-12 pcs 1W LED cool white strings in series and other external LED lmap of the same current and voltage

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST25W-AP36700	100-240VAC	DC 21-36V	700mA±3%	7-10*3W	90%	0.97	1-500pcs		
DST25W-AP50500	100-240VAC	DC 30-50V	500mA±3%	10-15*2W	90%	0.97	500-1Kpcs		
DST25W-AP50420	100-240VAC	DC 30-50V	420mA±3%	10-15*1.5W	90%	0.97	1K-2Kpcs		
DST25W-AP80300	100-240VAC	DC 50-80V	300mA±3%	15-25*1W	90%	0.97	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L140mm * W45mm * H28mm	SAA/SGS/PSE/TUV/RoHS		TERMINAL		Isolation circuit			130g	

Waterproof... It is especially designed for LED floodlamps, wall lamps, spotlights and singal lights. The street lamp are waterproof LED. Imported chis with good stability. Smart and elegant. High constand current accuracy. High efficiency. Stable ability. Low noise and long life. It can directly driver 16-25 pcs 1W LED cool white strings in series and other external LED lmap of the same current and voltage

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST35W-AP36900	100-240VAC	DC 21-36V	900mA±3%	8-10*4W	90%	0.97	1-500pcs		
DST35W-AP50500	100-240VAC	DC 30-50V	700mA±3%	10-15*3W	90%	0.97	500-1Kpcs		
DST35W-AP95300	100-240VAC	DC 30-50V	300mA±3%	25-33*1W	90%	0.97	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L140mm * W45mm * H30mm	SAA/SGS/PSE/TUV/RoHS		TERMINAL		Isolation circuit			150g	

This product is using card and buckle design. It is especially designed for LED ceiling lamps and downlights. Flood lamps and other LED lightings. Imported chips with stability. Smart and elegant. Good and accurate constant current in high accuracy. High efficiency good stability. Full protection abilities. High and good advantages. Low noise, Long life. There can drive 26-35pcs in 1W in Cool white LED strings and other external LED lamps of the same current and voltage.

WATERPROOF LED DRIVER

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST9W-AW30320	100-240VAC	DC 12-30V	320mA±3%	4-9*1W	75%	0.75	1-500pcs		
							500-1Kpcs		
							1K-2Kpcs		
Dimension	Certified		Hard wire		Waterproof Grade			Weight	
L58mm * W30mm * H25mm	SGS/RoHS		4WIRE		IP65			150g	


This is designed for LED ceiling lmaps and downlights. Could be ised both waterproof & non-waterproof. Imported chips with stability. stable function Smart and elegant. with constant current. High efficiency good stability. Full protection abilities. High and good advantages. Low noise, Long life. There can drive 4-9pcs LED stings of cool white 1W and other high power LED lamps of the same current and voltage.

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST25W-AWP36700	100-240VAC	DC 21-36V	700mA±3%	7-10*3W	90%	0.95	1-500pcs		
DST25W-AWP50500	100-240VAC	DC 30-50V	500mA±3%	10-15*2W	90%	0.95	500-1Kpcs		
DST25W-AWP80300	100-240VAC	DC 50-80V	300mA±3%	15-25*1W	90%	0.95	1K-2Kpcs		
Dimension	Certified		Hard wire		Waterproof Grade			Weight	
L200mm * W30mm * H20mm	UL/FCC/PSE/TUV/RoHS		4 WIRE		IP65			200g	

It is especially designed for LED floodlamps, wall lamps, spotlights and signal lights. the street lamps are waterproof LED. Imported chips with stability. Smart and elegant. Good and accurate constant current in high accuracy. High efficiency good stability. Full protection abilities. High and good advantages. Low noise, Long life. There can drive 16-25pcs in 1W in Cool white LED strings and other external LED lamps of the same current and voltage.


Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST35W-AW36900	100-240VAC	DC 21-36V	900mA±3%	8-10*4W	90%	0.97	1-500pcs		
DST35W-AW50500	100-240VAC	DC 30-50V	700mA±3%	10-15*3W	90%	0.97	500-1Kpcs		
DST35W-AW95300	100-240VAC	DC 80-100V	300mA±3%	25-33*1W	90%	0.97	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L85mm * W55mm * H35mm	UL/FCC/PSE/TUV/RoHS		4 WIRE		Isolation circuit			300g	

This product is especially designed for MR16 spotlight, it can realize low voltage adjustable silicone brightness adjustment according to electronic transformer It can realize LED lighting adjustment application needs according to low voltage brightness equipment.


Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST50W-AW66700	100-240VAC	DC 45-66V	700mA±3%	12-14*4W	90%	0.98	1-500pcs		
DST50W-AW401400	100-240VAC	DC 26-40V	1400mA±3%	7-12*1400mA	90%	0.98	500-1Kpcs		
DST50W-AW242000	100-240VAC	DC 16-24V	200mA±3%	5-7*200mA	90%	0.98	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L186mm * W50mm * H40mm	UL/FCC/PSE/TUV/RoHS		4 WIRE		Isolation circuit			800g	

This model is especially designed for street lamps. They are with high stability and can escape thunder stock. Good heat dissipation. High accurate DSTITAC power double craftsmanship. The wedge and feet points look like very neat. Full and clean high power factor design would escape the compulsory requirements to power supply system when government use LED street lamps. This power supply is inside metal cover or lamp body so that it can be waterproof.


OPEN FRAME CONSTANT CURRNET LED DRIVER

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST3W-HYG10300	100-240VAC	DC 3-11V	320mA±3%	1-3*1W	82%	0.65	1-500pcs		
							500-1Kpcs		
							1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L25mm * W15mm * H13mm	RoHS		4 WIRE		Isolation circuit			8g	


This driver is especially designed for GU10/E27/E26 LED spot lights. It has high conversion efficiency. It can reach 82% in 220VAC and 84% in 110VAC. High efficiency could reduce costs and avoid temperature arising so that the electrical circuit could be re - used

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST5W-HYG10420	100-240VAC	DC 7-11V	420mA±3%	3*2W	82%	0.65	1-500pcs		
DST5W-HYG13340	100-240VAC	DC 10-14V	340mA±3%	4*.1W	82%	0.65	500-1Kpcs		
DST5W-HYG16270	100-240VAC	DC 10-16V	270mA±3%	5*1W	82%	0.65	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L26mm * W15mm * H15mm	RoHS		4 WIRE		Isolation circuit			8g	


This driver is especially designed for GU10/E27/E26 LED spot lights. It has high conversion efficiency. It can reach 85% in 220V/ 110VAC. High efficiency could reduce costs and avoid temperature arising so that the electrical circuit could be re - used

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST7W-HYG23320	100-240VAC	DC 12-25V	320mA±3%	4-7*1W	86%	0.65	1-500pcs		
							500-1Kpcs		
							1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L35mm * W17.50mm * H17mm	RoHS		4 WIRE		Isolation circuit			25g	


This driver is especially designed for GU10/E27/E26 LED spot lights. It has high conversion efficiency. It can reach 85% in 220V/ and 86% in 110VAC. High efficiency could reduce costs and avoid temperature arising so that the electrical circuit could be re - used

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST10W-HYG10600	100-240VAC	DC 9-12V	600mA±3%	2-3*3W	86%	0.65	1-500pcs		
DST10W-HYG10450	100-240VAC	DC 9-12V	450mA±3%	2-3*2W	86%	0.65	500-1Kpcs		
DST10W-HYG36300	100-240VAC	DC 15-36V	300mA±3%	5-10*1W	86%	0.65	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L38mm * W16mm * H21mm	RoHS		4 WIRE		Isolation circuit			15g	


This driver is especially designed for GU10/E27/E26 LED spot lights. It has high conversion efficiency. It can reach 85% in 220V and 86% in 110VAC. High efficiency could reduce costs and avoid temperature arising so that the electrical circuit could be re - used

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST3W-HYG10300	100-240VAC	DC 5-11V	300mA±3%	3*1W	73%	0.65	1-500pcs		
							500-1Kpcs		
							1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L25mm * W17mm * H15mm	RoHS		4 WIRE		Isolation circuit			8g	


This driver is especially designed for GU10/E27/E26 LED spot lights. It is with high efficiency and low defective rate. It has safety requirement and interference design could assure European countries's safety requirements.

Product Name	Input Voltage	Output Voltage	Type Current	Paralle/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST6W-HYG10600	100-240VAC	DC5-11V	600mA±3%	2-3*3W	76%	0.75	1-500pcs		
DST6W-HYG10450	100-240VAC	DC 5-11V	450mA±3%	2-3*2W	76%	0.75	500-1Kpcs		
DST6W-HYG20320	100-240VAC	DC 12-20V	320mA±3%	4-6*1W	76%	0.75	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
L51mm * W20mm * H16mm	EMC/EMI/PSE/RoHS		4 WIRE		Isolation circuit			15g	


This product especially designed for GU1-/E27/E26 LED bulb. The great advantages are that it compliance with EMC and high stability. The mature application examples can assure 1000/1 indefective percentages. The neat clean and good craftsmanship can assure the imported IC:s working conditions. It can avoid the re-assembling time and reduce labour costs.

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST9W-AG10600	100-240VAC	DC 5-11V	600mA±3%	2-3*3W	85%	0.75	1-500pcs		
DST9W-AG10500	100-240VAC	DC 5-14V	500mA±3%	2-4*2W	85%	0.75	500-1Kpcs		
DST9W-AG30300	100-240VAC	DC 20-40V	300mA±3%	6-9*1W	85%	0.75	1K-2Kpcs		
DST9W-AG40240	100-240VAC	DC 20-40V	240mA±3%	9-12*1W	85%	0.75			
Dimension	Certified		Hard wire		Circuit type			Weight	
L26mm * W15mm * H15mm	EMC/EMI/PSE/RoHS		4 WIRE		Isolation circuit			18g	

This product especially designed for GU1-/E27/E26 LED bulb. The outstanding advantage is that it can pass CE and high conversion efficiency. If input voltage is 220VAC. It can be 85% efficiency, if input voltage 110VAC it can be 86% efficiency. The high conversion efficiency can reduce costs and avoid temperature arising. The electrical circuit could be reliably re-used, the safety requirements to CE and non interference designs could compliance with the application needs in European countries.

MR16 CONSTANT CURRENT LED DRIVER									
Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST3W-MR-G03600	12/24VAC	DC 2-5V	600mA±3%	1*3W	90%	0.65	1-500pcs		
DST3W-MR-G03600	12/24VAC	DC 2-5V	300mA±3%	3*1W	90%	0.65	500-1Kpcs		
DST3W-MR-G03600	12/24VAC	DC 2-5V	500mA±3%	3*2W	90%	0.65	1K-2Kpcs		
DST3W-MR-G03600	12/24VAC	DC 2-5V	600mA±3%	3*3W	90%	0.65			
Dimension	Certified		Hard wire		Circuit type			Weight	
L14mm * W12mm * H18mm	CE/RoHS		MR16		Bulk circuit			3g	

Designed for MR16 spotlight. It can make dimming performance with ordinary all electronics dimmers

Product Name	Input Voltage	Output Voltage	Type Current	Parallel/Series	Efficiency	Power Factor	Quantity	Price (USD)	Picture
DST2W-AR111-40320	12VAC	DC 21-40V	320mA±3%	6-12*1W	87%	0.65	1-500pcs		
DST2W-AR111-30500	12VAC	DC 15-30V	500mA±3%	4-6*2W	87%	0.65	500-1Kpcs		
DST2W-AR111-40380	12VAC	DC 20-40V	380mA±3%	4-12*2W	87%	0.65	1K-2Kpcs		
Dimension	Certified		Hard wire		Circuit type			Weight	
ø44mm * H16mm	CE/RoHS		4 WIRE		Isolation circuit			50g	

Designed for AR111 which need high and design requirements and applications. It has sink pcs at the bottom. The outstanding outlook is great. The outstanding character is high onversion efficiency and high life (50,000hrs). The low voltage dimmable version would be introduced.

Product and question remarks

1. Quotation based on USD.
2. Quotation valid date is 1 months
3. Private packing available from 300pcs order / lot.
4. Guarantee 2 years for our
We will change goods months after sales shall there are problem caused by us
5. Quotation condition: EX-work,
6. All theraw mateial are used good quality ones to assure reliable quality and stability. Pls. feel free to contact us for concered product certificates.
7. WE can use Rubycon, Bingfeng capacitors according to customer's request
8. For the new products we need 10-15days as products development date.
9. Packing: standard export packing. Private packing available as option by custome's requirements
10. The above products are accoding to cool white LED VF. Regarding to yellow, blue and green LED , will not classify. Pls take reference to the input voltahe list

DSTITAC Power - Booster inside