



DSTiTAC

LED High bay Lights


High Bay Lighting....



THBC-30/60



Power (W)	Operating Voltage	Working Temp	Color Temp. (K)	CRI (Ra)	Lumen (lm)	Lifetime (h)	View Angle	Material
30	AC 85-265V 50Hz/60Hz	-10℃~+40℃	3000-7000	≥75	1900	>30000	90°	Aluminum Alloy
60	AC 85-265V 50Hz/60Hz	-10℃~+40℃	3000-7000	≥75	3500	>30000	90°	Aluminum Alloy



TLHB-30



Power (W)	Operating Voltage	Working Temp	Color Temp. (K)	CRI (Ra)	Lumen (lm)	Lifetime (h)	Fixture Dimensions(mm)	Weight (kg)	Material
30	AC 90-264V 50Hz/60Hz	-30℃~+50℃	3000-6500	≥80	3000-3300	>30000	270x448x186	4.2	Anodized Aluminum



TLHB-60



Power (W)	Operating Voltage	Working Temp	Color Temp. (K)	CRI (Ra)	Lumen (lm)	Lifetime (h)	Fixture Dimensions(mm)	Weight (kg)	Material
60	AC 90-264V 50Hz/60Hz	-30℃~+50℃	3000-6500	≥80	6000-6600	>30000	355x448x186	5.8	Anodized Aluminum



TLHB-90



Power (W)	Operating Voltage	Working Temp	Color Temp. (K)	CRI (Ra)	Lumen (lm)	Lifetime (h)	Fixture Dimensions(mm)	Weight (kg)	Material
90	AC 90-264V 50Hz/60Hz	-30℃-+50℃	3000-6500	≥80	9000-9900	>30000	440x448x186	7.8	Anodized Aluminum



TLHB-120



Power (W)	Operating Voltage	Working Temp	Color Temp. (K)	CRI (Ra)	Lumen (lm)	Lifetime (h)	Fixture Dimensions(mm)	Weight (kg)	Material
120	AC 90-264V 50Hz/60Hz	-30℃-+50℃	3000-6500	≥80	12000-13200	>30000	525x448x186	9.2	Anodized Aluminum



TLHB-150



Power (W)	Operating Voltage	Working Temp	Color Temp. (K)	CRI (Ra)	Lumen (lm)	Lifetime (h)	Fixture Dimensions(mm)	Weight (kg)	Material
150	AC 90-264V 50Hz/60Hz	-30℃-+50℃	3000-6500	≥80	15000-16500	>30000	610x448x186	10.7	Anodized Aluminum



TLHB-180



Power (W)	Operating Voltage	Working Temp	Color Temp. (K)	CRI (Ra)	Lumen (lm)	Lifetime (h)	Fixture Dimensions(mm)	Weight (kg)	Material
180	AC 90-264V 50Hz/60Hz	-30℃-+50℃	3000-6500	≥80	18000-19800	>30000	695x448x186	12.3	Anodized Aluminum